

AASHTO T 283

Pavegrip PA-30

High Performance
Antistripping Additive

SUPERPAVE

Pavegrip – GET A GRIP ON THE REQUIRED TSR OF TODAYS TOUGH MIX DESIGNS

Product: Pavegrip PA-30 is a concentrated 100% active liquid antistripping additive. It's 100% active formulation makes this low odor, heat stable product a high performance additive that can help with even the most difficult mix designs.

Benefits: SUPERPAVE Moisture Sensitivity Testing - Significantly improves Tensile Strength Ratio results in the AASHTO T-283 test procedure

Easy to use liquid – Unlike lime, it does not increase dust content and lower the voids in the mineral aggregate (VMA). Also, being a liquid it can be metered or pumped using a gear or displacement pump.

**Recommended:
Dosage** 0.25% to 0.75% based upon the weight of the liquid asphalt cement.

Properties:	Viscosity @ 77°F cs	100- 200
	Specific Gravity @ 77°F	1.12 ± 0.04
	Weight, lbs/gal @ 77°F	9.30 ± 0.33
	Flash Point (ASTM D92)	342°F
	Pour Point (ASTM D97)	4°C/40°F

**Storage and
Handling** Always refer to the product MSDS prior to handling. Pavegrip PA-30 is NOT a DOT regulated product. It can be stored in a mild steel tank. The recommended storage temperature is 100° to 120° F. Packaging includes 55 gallon drums (480 pounds net), 275 gallon totes (2,400 pounds net) or in various bulk quantities.