

AASHTO T 283



SUPERPAVE

Pavegrip – GET A GRIP ON THE REQUIRED TSR OF TODAY'S TOUGH MIX DESIGNS

Product: Pavegrip 550 LV is a concentrated 100% active liquid antistripping additive. It's 100% active formulation makes this low odor, heat stable product a high performance additive that can help with even the most difficult mix designs.

Benefits: SUPERPAVE Moisture Sensitivity Testing - Significantly improves Tensile Strength Ratio results in the AASHTO T-283 test procedure

Easy to use liquid – Unlike lime, it does not increase dust content and lower the voids in the mineral aggregate (VMA). Also, being a liquid it can be metered or pumped using a gear or displacement pump.

Recommended Dosage: 0.25% to 0.75% based upon the weight of the liquid asphalt cement.

Properties:	Viscosity @ 77°F cs	150 – 50
	Specific Gravity @ 77°F	1.02 ± 0.04
	Weight, lbs/gal @ 77°F	8.50 ± 0.33
	Flash Point (ASTM D92)	359°F
	Pour Point (ASTM D97)	10°C/50°F

Storage and Handling Always refer to the product MSDS prior to handling. Pavegrip 550 LV is a DOT regulated product. Pavegrip 550 LV can be stored in a mild steel tank. The recommended storage temperature is 100° to 120° F. Packaging includes 55 gallon drums (440 pounds net), 275 gallon totes (2,205 pounds net) or in various bulk quantities.